

SECURINESS

Eastimage 8065



www.securiness.com 🥻 Kontakt os venligst for mere information

SECURINESS – Your baggage inspection expert.





SECURINESS Eastimage Model 8065

General Specifications

Tunnel Size 810mm (W) \times 650 mm (H) / 32"(W) x 26" (H)

Conveyor Speed 0.2 m/sConveyor Max. Load 200kg

Wire Resolution Dia 0.13mm (36 AWG) metal wire

Penetration 30 mm steel

Film Safety Guaranteed up to ISO1600

X-ray Dose Less than 1 μGy/h (5cm from shell of radiation source)

X-ray Generator

Beam Direction Downward Tube Voltage 140kV

Cooling/Duty Cycle Sealed Oil Cooling - 100%



Options

Crisis Analysis System (Black Box)

X-Ray Automatic Recognition Software System for inspecting suspicious explosive and drugs (X-Autosight)

Threat Image Projection (TIP)
Operator Training Program (OTP)
Baggage Overview Device (BOD)
Entry / Exit Roller Tables
UPS/Stabilized Voltage Supply

Image System

X-ray Detector L-shape photodiode array

Monitor 1280 X 1024 high resolution color monitor

Image Display Mode B/W, pseudo color, multi energy

Image transformation Color / black & white image, negative, edge enhancement, image strengthening, Organic/Inorganic compound rejecting, grey level scanning, image recall, suspicious

object alarm and image retrieval Image Grey Level 4096

Image Processing 24bit real time processing

Image Storage Storage 20000 pictures in real time

Zoom Up to 16 times enlargement

Other Functions Date & time display, running status indication, eagle-eye function, operator identification code, baggage counting, emergency stop, self diagnosis, network interface,

system running timer and x-ray on timer

Installation Requirements

Operation Power 220 VAC (+10%~-15%) /50+3Hz

Max. Power 1.4 KVA

System solutions

For yderligere information, kontakt os venligst på info@securiness.com.

