

# EI-MD3000

# Walkthrough Metal detector



Specifications are subject to change 🥻 Kontakt os venligst for mere information

## High Sensitivity Digital Walkthrough Metal Detector.

### **Product Introduction**

EI-MD3000 high sensitivity digital walkthrough metal detector use excellent electromagnetic testing and digital processing technology, has high detection sensitivity of the magnetic metal and nonmagnetic metal, and good recognition for personal items such as coins, keys, belt buckle, etc. Have multi-zone technology, 24 detection zones.

#### Main Features

- ◆ Small metal like a paper clip can be detected; suitable for high level security inspection
- ◆ With multi-zone high-brightness LED lights and indicate accurate location with sound
- ♦ Combine digital and simulated technology, super high anti-interference ability, reduce the error alarm
- ◆ Strong ability for self-diagnosis; running status monitoring; error alarm with sound and light
- ◆ The outer cover is made of high strength material, which has a strong capability of waterproof, fireproof, anticorrosion and shockproof
- ◆ Modular design, easy installation and maintenance
- ◆ TCP/IP network function

#### Technology Data

♦ Detection SensitivityA paper clip can be detected, sensitivity controllable			
	♦ Sensitivity Level Adjustable 0~255 levels sensitivity in each detecting zone; Effective sensitivity 255 levels in the whole unit		
	♦ Detecting zoneAccurate alarm in single or multi-zone according to requirements		
	♦ Display MonitorHigh-brightness LCD Screen		
	♦ Audible alarm		
	♦ Light warning barMulti-zones high-brightness LED light-warning		
	♦ Operation authorizationPassword protection, authorization using only		
	♦ Counter100% accurate counting on alarming time		

- Factory default resetting......Quick reset Factory default
- ♦ Alarm.....Voice and light



### **Installation Data**

♦ Size	2230mm (L)*830mm (W)*580mm (H)
♦ Tunnel Size	2000mm (L)*700mm (W)*500mm (H)
♦ Power Supply	AC150V~242V/50+5%HZ
♦ Power Consumption	13.9W
♦ Working Temperature	20℃~+55℃
♦ Weight	Approx.65kg



