



SECURINESS

EastImage 6550

www.securiness.com  Kontakt os venligst for mere information

SECURINESS – Your baggage inspection expert.
We provide all clients with distinguishing features of baggage inspection based on advanced technology, excellent products and professional service.



SECURINESS EastImage Model 6550

General Specifications

| | |
|--------------------|--|
| Tunnel Size | 650mm (W) × 500 mm (H) / 26"(W) x 20" (H) |
| Conveyor Speed | 0.2 m/s |
| Conveyor Max. Load | 160kg |
| Wire Resolution | Dia 0.101mm (38 AWG) metal wire |
| Penetration | 30 mm steel |
| Film Safety | Guaranteed up to ISO1600 |
| X-ray Dose | Less than 1 µGy/h (5cm from shell of radiation source) |

X-ray Generator

| | |
|--------------------|---------------------------|
| Beam Direction | Upward |
| Tube Voltage | 140kV |
| Cooling/Duty Cycle | Sealed Oil Cooling - 100% |

Options

Crisis Analysis System (Black Box)

X-Ray Automatic Recognition Software System for inspecting suspicious explosive and drugs (X-Autosight)

Threat Image Projection (TIP)

Operator Training Program (OTP)

Baggage Overview Device (BOD)

Entry / Exit Roller Tables

UPS/Stabilized Voltage Supply

Image System

| | |
|----------------------|--|
| X-ray Detector | L-shape photodiode array |
| Monitor | 1280 X 1024 high resolution color monitor |
| Image Display Mode | B/W, pseudo color, multi energy |
| Image transformation | Color / black & white image, negative, edge enhancement, image strengthening, Organic/Inorganic compound rejecting, grey level scanning, image recall, suspicious object alarm and image retrieval |
| Image Grey Level | 4096 |
| Image Processing | 24bit real time processing |
| Image Storage | Storage 20000 pictures in real time |
| Zoom | Up to 16 times enlargement |
| Other Functions | Date & time display, running status indication, eagle-eye function, operator identification code, baggage counting, emergency stop, self diagnosis, network interface, system running timer and x-ray on timer |

Installation Requirements

| | |
|-----------------|-----------------------------|
| Operation Power | 220 VAC (+10%~-15%) /50+3Hz |
| Max. Power | 1.0 KVA |

Alternative modeller i serien

6550 HR

Conveyor Speed - 0.2 m/s, Conveyor Max. Load - 160kg, Wire Resolution - Dia 0.078mm (40 AWG) metal wire, Penetration - 32 mm steel

6550B

Conveyor Speed - 0.2 m/s, Conveyor Max. Load - 160kg, Wire Resolution - Dia 0.101mm (38 AWG) metal wire, Penetration - 30 mm steel

6550B HR

Conveyor Speed - 0.2 m/s, Conveyor Max. Load - 160kg, Wire Resolution - Dia 0.078mm (40 AWG) metal wire, Penetration - 32 mm steel

System solutions

For further information please mail to info@securiness.com.

