



SECURINESS

Eastimage MD3000A










www.securiness.com  Kontakt os venligst for mere information

High Sensitivity Digital Walkthrough Metal Detector



SECURINESS Eastimage Model MD3000A

Technology features

-  High detection sensitivity for the magnetic metal, non-magnetic metal and alloy
-  Self diagnostic program, power-on self test, modular structure, multi-language selection, the system automatically wake up
-  Highly integrated DSP digital processing technology, no need of tools to adjust, performance is more stable, more convenient after-sales service
-  24 detecting area, each area can set sensitivity alone
-  Has 300 effective sensitivity
-  High-brightness color LCD; display function of power-on diagnose
-  30 preset detection programs
-  100 optional frequency
-  Real-time monitor of background environment interference

Technology data

Detection Sensitivity	24 detecting area, with high-brightness LED alarm, Precise positioning the location of hiding contraband.
Sensitivity Level	300 level adjustable for each detecting area
Frequency Setup	100 optional working frequency
Audible Alarm	20 volume levels adjustable, 16 tones levels adjustable
Display Screen	Color LCD display, Chinese/ English language select menu, Real-time display interference signal
Preset Working Model	30 security check working models, all parameters of detecting procedures can be set or modified at any time.
Operation Authorization	Password protection allows only authorized personnel operate
Throughput	100 people/min
Counting Function	Equipped with intelligent traffic and alarm counter, Real-time automatically displays the number of alarm and people, maximum100,000 records.
Energy-saving Function	The system will automatically enter power-saving mode when it is no detecting in 5 min., and will wake up when there is object.
Anti-interference	Highly integrated DSP digital processing technology Automatically detects environmental interference; Resistance to electromagnetic and mechanical interference; non-periodically calibration; no alarm errors caused by vibration and shaking.
Anti-interference Capability	50cm for devices adjacent side by side
Diagnostic function	Power-on self-test, fault Display, All-control information and settings can be operated on control panel and menu.

Procedure

Computer programming controller, Chinese and English optional language, modular structure

Safety

No harm to pacemaker wearers, Pregnant woman and magnetic media.

Installation data

Size	2200mm (L) * 800mm (W) * 550mm (H)
Tunnel Size	2000mm (L) * 700mm (W) * 500mm (H)
Power Supply	External power adapter, AC85-264V/47.5-60HZ
Power Consumption	<15W
Working Temperature	-20°C~ - +50°C
Weight	About 65 KG

System solutions

(Alle priser er eksklusive moms, levering og klargøring)

Pris

DKK

Ring venligst for pris