



# SECURINESS

## PocketHound

 Kontakt os venligst for mere information

### PocketHound Features

- Small enough to fit into your pocket or the palm of your hand
- Auto threshold sets detection level above ambient RF noise to avoid false triggering
- Perfect for cheating students, corporate espionage, courtroom and prisons too
- Detects phones up to 75 feet away indoors
- Internal, integrated flat antenna
- Superbright LEDs & vibration alerts all from within your pocket
- Receiver design boasts a dynamic range of -60 dB with user settable sensitivity
- User selectable up to -50dBm with a resolution of 2dB for detection in a noisy environment (typical of prisons)
- Detects all phones including 2G, 3G, 4G, CDMA, GSM, PCS, UMTS & more
- Selectivity rejection of at least 50 dB at 1 MHz from the uplink frequency bands provides high immunity from false triggering caused by base stations, personal communication devices and other sources of interference
- User selectable mobile frequency bands allow the same unit to be used around the world; both USA and European mobile uplink bands are supported
- Internal Li-ION battery runtime of 2 hours



EU / Asian / Australian / New Zealand / Canada / Israel      **WCDMA / UMTS** (1920-1980 MHz) Europe, Asia, Korea, Japan, Australia, Brazil, New Zealand

**GSM 1800** (1710.2-1784.8 MHz) Europe, Aisa, Japan

Bands Supported

**EGSM 900** (880-915 MHz) Europe, Asia, Australia, New Zealand

Radius of Coverage Area      75 feet (~25 meters) under typical conditions

Sensitivity Range      60 dB

Sensitivity      -80 dBm (user settable)

Selectivity Rejection      >50 dB @ 1 MHz uplinkband edges

Detector Resolution      2 dB

Bandwidth Resolution      4 MHz

Receiving Modes      High-speed scanning of uplink cellphone

Receiving Antennas Supported      Internal integrated flat panel antenna

USB      Mini-USB jack for charging only

Visual Alerts      Superbright LEDs



[www.securiness.com](http://www.securiness.com)

Tactile Inputs	2-way Slider Switch
Tactile Feedback	Integrated vibrator that increases with intensity as RSSI increases
Weight	Under 1 lb.
Dimensions	4" L x 3" W x 1" D
<b>OTHER FEATURES:</b>	
Integral Attenuator	0 to 30 dB, user-selectable via soft menu
Sensitivity Range	-80 to -50 dBm, user-selectable via soft menu
Data Logging	Integrated logging with built-in non-volatile memory and real time clock to allow recording and time-stamping detected signal events
Frequency Bands	Field-selectable via soft menu for versatile deployment around the globe over three different sets of frequency bands (US, EU cell phone uplink bands and DECT 6.0 band)
Internal Battery Runtime	Internal Li-Ion Polymer battery provides minimum run time of 2 hours
<b>INCLUDES:</b>	
Antenna	Internal
Retractable USB Cable	USB mini to standard
Charger	5VDC
Software	PC Configuration Software

## SECURINESS PocketHound

Kontakt os venligst for pris

Alle priser er eksklusive moms, levering og installation